

## Claims:

1. A transmission system for transmitting data between a first communication point and a second communication point along a link, comprising:

a plurality of media converters included in the link,

5 each of which comprises:

a first physical-layer interface to a first transmission medium;

a second physical-layer interface to a second transmission medium;

10 a memory connected between the first and second physical-layer interfaces, for temporarily storing data to be transferred between the first and second physical-layer interfaces; and

a media converter controller controlling such that, when  
15 a trigger signal has been received, a response block of data corresponding to the trigger signal is transmitted from a corresponding one of the first and second physical-layer interfaces back to a source that has transmitted the trigger signal; and

20 a test manager connected to one of the media converters, comprising:

an interface to a network manager; and

a test manager controller controlling such that a trigger

20140428 14:44:00

signal is transmitted to another media converter, and a location of a failure is determined depending on whether a response block of data is received from a corresponding media converter within a predetermined time period.

5           2.     The transmission system according to claim 1, wherein the first communication point is one of a plurality of ports of a switch and the second communication point is a personal computer, wherein the test manager is connected to a media converter which is directly connected to the switch.

10           3.     The transmission system according to claim 1, wherein the first communication point is one of a plurality of ports of a switch and the second communication point is a personal computer, wherein the test manager is implemented in a program-controlled processor of the switch to control a media  
15 converter which is directly connected to the switch.

          4.     The transmission system according to claim 1, wherein the test manager controller determines that a failure occurs at a location beyond the corresponding media converter when a response block of data is not received from a  
20 corresponding media converter within a predetermined time period.

          5.     The transmission system according to claim 1,

2013	2013
2014	2014
2015	2015
2016	2016
2017	2017
2018	2018
2019	2019
2020	2020
2021	2021
2022	2022
2023	2023
2024	2024
2025	2025
2026	2026
2027	2027
2028	2028
2029	2029
2030	2030
2031	2031
2032	2032
2033	2033
2034	2034
2035	2035
2036	2036
2037	2037
2038	2038
2039	2039
2040	2040
2041	2041
2042	2042
2043	2043
2044	2044
2045	2045
2046	2046
2047	2047
2048	2048
2049	2049
2050	2050
2051	2051
2052	2052
2053	2053
2054	2054
2055	2055
2056	2056
2057	2057
2058	2058
2059	2059
2060	2060
2061	2061
2062	2062
2063	2063
2064	2064
2065	2065
2066	2066
2067	2067
2068	2068
2069	2069
2070	2070
2071	2071
2072	2072
2073	2073
2074	2074
2075	2075
2076	2076
2077	2077
2078	2078
2079	2079
2080	2080
2081	2081
2082	2082
2083	2083
2084	2084
2085	2085
2086	2086
2087	2087
2088	2088
2089	2089
2090	2090
2091	2091
2092	2092
2093	2093
2094	2094
2095	2095
2096	2096
2097	2097
2098	2098
2099	2099
2100	2100
2101	2101
2102	2102
2103	2103
2104	2104
2105	2105
2106	2106
2107	2107
2108	2108
2109	2109
2110	2110
2111	2111
2112	2112
2113	2113
2114	2114
2115	2115
2116	2116
2117	2117
2118	2118
2119	2119
2120	2120
2121	2121
2122	2122
2123	2123
2124	2124
2125	2125
2126	2126
2127	2127
2128	2128
2129	2129
2130	2130
2131	2131
2132	2132
2133	2133
2134	2134
2135	2135
2136	2136
2137	2137
2138	2138
2139	2139
2140	2140
2141	2141
2142	2142
2143	2143
2144	2144
2145	2145
2146	2146
2147	2147
2148	2148
2149	2149
2150	2150
2151	2151
2152	2152
2153	2153
2154	2154
2155	2155
2156	2156
2157	2157
2158	2158
2159	2159
2160	2160
2161	2161
2162	2162
2163	2163
2164	2164
2165	2165
2166	2166
2167	2167
2168	2168
2169	2169
2170	2170
2171	2171
2172	2172
2173	2173
2174	2174
2175	2175
2176	2176
2177	2177
2178	2178
2179	2179
2180	2180
2181	2181
2182	2182
2183	2183
2184	2184
2185	2185
2186	2186
2187	2187
2188	2188
2189	2189
2190	2190

6. The transmission system according to claim 5,  
5 wherein the media converter controller accesses another one of  
the first and second physical-layer interfaces to acquire link  
information from the other physical-layer interface when the  
trigger signal has been received and generates the response  
block of data corresponding to the link information.

10           7.     The transmission system according to claim 5,  
wherein the test manager controller disables the missing link  
state when a test is started and forces a corresponding  
physical-layer interface into transmittable state to transmit  
the block of data to the link.

15           8.     The transmission system according to claim 5,  
wherein the media converter controller disables a missing link  
state when the trigger signal has been received, and transmits  
the response block of data to the source.

9. The transmission system according to claim 8,  
20 wherein when a received block of data is not a trigger signal  
under the missing link state, the media converter controller  
disables the missing link state to transfer the received block

of data to the other one of the first and second physical-layer interfaces.

10. A transmission system for transmitting data between a switching office and each of a plurality of subscriber devices, wherein the switching office comprises a switch having a plurality of ports corresponding to respective ones of the subscriber devices, wherein

the switching office further comprises:

a plurality of first media converters, each of which is connected to a different port of the switch at one end thereof through a metal cable and is connected to a different optical cable at the other end thereof; and

a test manager connected to each of the first media converters; and

each of the subscriber devices comprises:

a personal computer; and

a second media converter which is connected to the personal computer at one end thereof through a metal cable and is connected to a corresponding optical cable at the other end thereof,

wherein the test manager comprises:

an interface to a network manager; and

a test manager controller controlling each of the first media converters such that a trigger signal is transmitted to a corresponding second media converter, and a location of

a failure is determined depending on whether a response block of data is received from the corresponding second media converter within a predetermined time period, and

each of the second media converters comprises:

- 5 a first physical-layer interface to a metal cable;
- a second physical-layer interface to an optical cable;
- a memory connected between the first and second physical-layer interfaces, for temporarily storing data to be transferred between the first and second physical-layer
- 10 interfaces; and

- a media converter controller controlling such that, when the trigger signal has been received, a response block of data corresponding to the trigger signal is transmitted back to a corresponding first media converter that has transmitted the
- 15 trigger signal.

11. A media converter for converting from one type of media to another, comprising:

- first and second ports which are connected to the one type of media and the other type of media, respectively;
- 20 a packet buffer for storing a received packet; and
- a controller controlling such that, when a link on the first port is disconnected, another link on the second port is kept in a connection state and a packet received through the second port is stored in the packet buffer.

12. A media converter for converting from one type of media to another, comprising:

a first physical-layer interface to a first transmission medium;

5 a second physical-layer interface to a second transmission medium;

a first memory connected between the first and second physical-layer interfaces, for temporarily storing data to be transferred between the first and second physical-layer  
10 interfaces;

a second memory included in at least one of the first and second physical-layer interfaces, for storing data received through a corresponding one of the first and second physical-layer interfaces; and

15 a controller controlling such that, when a link on one of the first and second physical-layer interfaces is disconnected, another link on the other one of the first and second physical-layer interfaces is kept in a connection state and data received through the other link is stored in the  
20 second memory.

13. The media converter according to claim 12, wherein each of the first and second physical-layer interfaces supports MII (Media Independent Interface) conforming to IEEE802.3 standards.

14. The media converter according to claim 12, wherein the controller further accesses the one of the first and second physical-layer interfaces to acquire link information and transmits the link information through the other one of the first  
5 and second physical-layer interfaces.

15. The media converter according to claim 12, wherein the controller further accesses the second memory to read the stored data when the link on the one of the first and second physical-layer interfaces has been restored, and transmits the  
10 stored data through the one of the first and second physical-layer interfaces.

16. A control method for a media converter for converting from one type of media to another, wherein the media converter comprises:

15 a first physical-layer interface to a first transmission medium;

a second physical-layer interface to a second transmission medium;

a first memory connected between the first and second  
20 physical-layer interfaces, for temporarily storing data to be transferred between the first and second physical-layer interfaces; and

a second memory included in at least one of the first and second physical-layer interfaces, for storing data received

through a corresponding one of the first and second physical-layer interfaces,

the control method comprising the steps of:

a) monitoring the first and second physical-layer  
5 interfaces to determine whether a link is disconnected;

b) when a link on one of the first and second physical-layer interfaces is disconnected, keeping another link on the other one of the first and second physical-layer interfaces in a connection state;

10 c) when data has been received through the other link on the other one of the first and second physical-layer interfaces, storing the received data in the second memory.

17. The control method according to claim 16, further comprising the steps of:

15 d) accessing the one of the first and second physical-layer interfaces to acquire link information in response to a link information request received from outside; and

e) transmitting the link information in a  
20 predetermined signal format through the other one of the first and second physical-layer interfaces.

18. The control method according to claim 16, further comprising the steps of:

f) when the link on the one of the first and second



physical-layer interfaces has been restored, accessing the second memory to read the stored data; and

g) transmitting the stored data through the one of the first and second physical-layer interfaces.

5           19. A transmission system comprising:

first end device and second end device which are connected to each other by a link through a plurality of media converters, wherein at least one of the media converters comprises a packet buffer for storing a received packet, wherein  
10 the packet buffer divides the link into a first collision domain of the first end device and a second collision domain of the second end device.

20. The transmission system according to claim 19, wherein said least one of the media converters further comprises  
15 a controller controlling such that, when a link on one port thereof is disconnected, another link on the other port is kept in a connection state and a packet received through the second port is stored in the packet buffer.

21. The transmission system according to claim 19,  
20 wherein when one of the first and second collision domains becomes in a link disconnection state, the other one of the first and second collision domains is kept in a link connection state and normal communication is performed between a media converter

20040418 010900

and a corresponding end device in the other one of the first and second collision domains.

22. A transmission system comprising:

a first media converter installed in a subscriber

5 house; and

a second media converter installed in a switching office, wherein the second media converter is connected to the first media converter by an optical fiber cable,

10 wherein the first media converter comprises a packet buffer for storing a received packet, wherein a missing link function is released to keep a link to the switching office in a connection state regardless of a state of a link to the subscriber house.

1004043 01050